

PA 1142771

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 11, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/466,309 ✓

FILING DATE: April 29, 2003 ✓

EP 2004/2188 ✓

PRIORITY DOCUMENT


SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 31 MAR 2004

WIPO

PCT

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



P. SWAIN
Certifying Officer

04-30-03 60/466309-04-29-03 APPROV

04/29/03
3860 U.S. PTO

orney's Docket No. 9342-86PR

PATENT

**COVER SHEET FOR FILING PROVISIONAL
PATENT APPLICATION (37 CFR §1.51(c)(1))**

3860 U.S. PTO
60/466309
04/29/03

PROVISIONAL PATENT APPLICATION

Commissioner for Patents
Washington, DC 20231

Date: April 29, 2003

This is a request for filing a PROVISIONAL PATENT APPLICATION under 37 C.F.R. §1.53(c).

Docket No.	9342-86PR
Type a plus sign (+) inside this box ☐	+

INVENTOR(s)/APPLICANT(s)

Name: Zhingong Ying
Address: Skyttelinjen 50
S-226 49 Lund
SWEDEN

TITLE OF THE INVENTION (280 characters maximum)

ANTENNA DEVICE FOR COMMUNICATION EQUIPMENT

ENCLOSED APPLICATION PARTS (check all that apply)

- ☒ Specification (Number of Pages 11)
- ☒ Drawing(s) (Number of Sheets 3)
- ☐ Claims (Number of Claims)
(A complete provisional application does not require claims 37 C.F.R. §1.51(c)).
- ☐ Application Data Sheet. See 37 CFR §1.76
- ☐ Other:

In re: Ying
Filed: Concurrently Herewith
Page 2

CORRESPONDENCE ADDRESS



20792

PATENT TRADEMARK OFFICE

METHOD OF PAYMENT

- ☐ Applicant claims small entity status. See 37 CFR §1.27.
☒ Check or money order is enclosed to cover the filing fee.
☐ Payment by credit card. Form PTO-2038 is attached.
☐ The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account No. 50-0220.

* The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

- ☒ No.
☐ Yes, the name of the U.S. Government agency and the Government contract number are:

Respectfully submitted,

Robert W. Glatz

Registration No. 36,811

CERTIFICATE OF EXPRESS MAIL

Express Mail Label Number EV 193585557 US

Date of Deposit: April 29, 2003

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to Box PROVISIONAL PATENT APPLICATION, Commissioner for Patents, Washington, DC 20231.

Carcy Gregory

ANTENNA DEVICE FOR COMMUNICATION EQUIPMENT

Technical Field of the Invention

5 The present invention relates generally to an antenna for a card device. More particularly, the invention relates to an antenna device having a pattern of conductive material for establishing a wireless communication link.

Description of Related Art

10 Computers are utilized for accessing different communication networks, such as a Local Area Network (LAN), a Wireless Local Area Network (W-LAN), a Wide Area Network (WAN), and/or a telecommunication network. Conventionally, a connection has been established through a wire-based
15 connection, such as a serial cable. It is increasingly common that a computer is provided with a card slot, in which interchangeable computer cards may be inserted. Standards for such PC cards are provided by the Personal Computer Memory Card International Association (PCMCIA).
20 PCMCIA standards specify spatial size restrictions and coupling interface restrictions for computer cards that embody peripheral devices, such as network interface cards. The PCMCIA standards enable a computer user to selectively use a first peripheral device and later remove it when it
25 is no longer needed. This is particularly useful because it allows the computer user to change to another peripheral device based on particular needs. A computer user may e.g. first access data stored on an auxiliary memory card and later exchange the memory card for a network interface card
30 to access a LAN.

The network interface card may be provided with a wireless interface for accessing a communication network. A computer card having a wireless interface requires some sort of antenna. Antennas known in the art are external
35 antennas attached to the housing of the card. This is a problem as the external antennas often are bulky. The

external antennas are sometimes detachable to provide a less bulky card during storage and when not in operation. This causes a problem in that the user has to keep track of two separate items, the card and the antenna.

5 A further problem with the known cards is that the bulky antennas make them inconvenient to insert and retract from a card slot of a computer. The geometrical shape of the card device is limited by the external antenna.

The external antenna may be provided as a foldable whip antenna. However, there is a problem with a foldable antenna as its position during operation may be displaced, which may cause performance degradation.

10 US-6 329 962 discloses a multiple band antenna having multiple branches. Each branch can be formed by a flexible film, which has a meandering, outer spiral or inner spiral strip line pattern formed thereon. Each branch can also be formed by etching a strip line to a member of a desired shape.

20 Summary of the Invention

It is a first object of the invention to provide an antenna device for communication equipment, such as a card device for a computer, which is not bulky in operation.

25 It is a second object of the invention to provide an antenna device having an antenna, which provides for great design flexibility of the housing of the communication equipment.

A third object of the invention is to provide an antenna device having a nice design and low cost of manufacturing.

30 The above objects are achieved by an antenna device for a portable communication equipment having a housing, comprising: at least a first antenna arranged on a support element, and antenna output means. The geometric shape of the support element is conformed to the geometric shape of

35

a protruding member of the housing. Moreover, the geometric shape of the support element may be conformed to the geometric shape of an inner surface of the protruding member.

- 5 The antenna device may comprise at least a second antenna arranged on the support element. The first or the second antenna may be formed as printed traces of conductive material on the support element.

- 10 The support element may comprise a flexible dielectric film. Alternatively, the support element may be an inner surface of the protruding member.

- 15 The first antenna may be a multiple branch antenna. The second antenna may be a diversity antenna having first and second monopole antenna branches provided with a mutual distance of at least a quarter of a wavelength of the signal for which the second antenna is adapted. The first antenna may be tuned to a predetermined first frequency and the second antenna may be tuned to a predetermined second frequency. More specifically, the first antenna may be adapted for communication in a GSM frequency band, a DCS frequency band, a PCS frequency band, and/or a UMTS frequency band. The second antenna may be adapted for communication in a W-LAN frequency band.

- 20 Another object of the invention is to use the inventive antenna device in a communication apparatus having a design for easy operation, such as insertion and retraction into/out from a card slot.

- 25 This object is achieved by using the inventive antenna device in a portable communication equipment. The portable communication equipment may be a computer card device for providing wireless data communication.

30 One advantage of the present invention is that the antenna device provides great flexibility for the geometric shape of the housing of the card device. Also, a user of

the card does not have to take any bulky external antenna into consideration.

Furthermore, it is an advantage that the antenna device can be integrated within the housing of the card device, specifically in the protruding member.

5 Incorporating the antenna device into the protruding member may provide two functions in one structural means, a handle means and an antenna.

Further embodiments of the invention are defined in

10 the dependent claims.

It should be emphasized that the term "comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or

15 addition of one or more other features, integers, steps, components or groups thereof.

Brief Description of the Drawings

Further objects, features, and advantages of the invention will appear from the following description of

20 several embodiments of the invention, wherein various aspects of the invention will be described in more detail with reference to the accompanying drawings, in which:

Fig. 1 is a schematic perspective view of a computer

25 card device having a protruding member comprising an antenna device according to the invention, as well as an example of an environment in which it may operate;

Figs. 2a-c are side views of the card device, which show alternative embodiments of the geometrical shape of

30 the protruding member;

Fig. 3 is a front view of a first embodiment of the antenna device according to the invention; and

Fig. 4 is a front view of a second embodiment of the antenna device according to the invention.

Detailed Description of Embodiments

Fig. 1 illustrates a computer card device 1 having computer module dimensions, such as a PCMCIA (Personal Computer Memory Card International Association) computer card device. The card device 1 is capable of establishing a communication link with a server 2 of a W-LAN (Wireless Local Area Network), via a first wireless link 3. The card device 1 may also establish a second wireless link 4 with a radio station (base station) 5 in a mobile telecommunication network 6, such as a GSM, DCS, PCS, UMTS and/or cdma2000 network.

The card device comprises a housing 10 having an integrated protruding member 11 for providing e.g. a handle means. The protruding member 11 provides easy operation for inserting and retracting the card device 1 into/out from a mating card slot of an electronic apparatus, such as a desktop computer or a laptop computer, having a PCMCIA card slot. At one end of the housing 10, preferably at the opposite end of the protruding member 11, is a connector interface 12 provided. The interface 12 will mate with a connector interface of a corresponding card device slot extending into the interior of the electronic apparatus when the card device 1 is inserted therein. The card device 1 is adapted to communicate data with the apparatus it is inserted in.

In Figs. 2a-c, different embodiments of the protruding member 11 are illustrated. Fig. 2a is a side view of the card device of Fig. 1, wherein the protruding member 11 extends in the direction of insertion and retraction (X) of the card device 1 into the card slot of the electronic equipment. The protruding member 11 may be made of a rubber material, which is connected to the housing 10. Alternatively, the protruding member 11 is provided in the same material as the housing 10, and is an extension of the housing 10, with which it forms an

integral unit. The housing 10 may be made of a plastic or rubber material.

5 The angle of the protruding member 11 relatively to the housing 11 is not limited to the direction of insertion and retraction (X), as is indicated with a L-shaped protruding member 20 in Fig. 2b. The angle of the protruding member 11 relatively to the housing 10 and the direction of insertion and retraction X may be in the range of +/- 90 degrees.

10 Fig. 2c is a side view of a third embodiment of the card device 1 having a corrugated protruding member 30. The corrugated protruding member 30 may be provided according to the same principles as the protruding members 11, 20 of Figs. 1-2. Consequently, the corrugated protruding member
15 30 may be provided in different angles with respect to the housing 10.

The geometric shape of the protruding member 11, 20, 30 is not limited to the shown embodiments. Said shape may be varied in a number of ways for providing a protruding
20 member that provides an efficient and convenient means for inserting/retracting the card device 1 into/from the card slot of the computer. Furthermore, the shape may vary due to design considerations, such as radiation characteristics.

25 Fig. 3 illustrates a first embodiment of the antenna device according to the present invention. The antenna device comprises at least a first antenna 110 formed as a trace of conducting material on a support element 111. The first antenna is a multi band branch antenna comprising a
30 first and a second branch 112, 113 formed by strips of conducting material. The length of the branches 112, 113 is selected so as to allow said multiple branch antenna 110 to be tuned to multiple resonance frequencies at first and second frequency bands. The first band may be the GSM 900
35 MHz frequency band and the second band may be the GSM

1800/1900 GSM frequency band. The length of the first branch is approximately $\frac{1}{4}$ wavelength of a GSM 900 MHz signal, and the second branch is approximately a $\frac{1}{4}$ wavelength of a GSM 1800/1900 MHz signal. Alternatively,
 5 either of the bands may be the DCS, PCS or the UMTS frequency band.

The first and the second branches 112, 113 are connected to each other. The first antenna 110 comprises a terminal 114 for exchanging signals with
 10 receiver/transmitter circuitry within the card device 1. The first branch 112 is an outer spiral branch strip, which resonates at first frequencies. The second branch 113 is a meandering branch, which resonates at second frequencies. Alternatively, the branches are formed as inner spiral
 15 branches. A variety of different patterns for the branches 112, 113, and possibly additional branches when appropriate, could be selected to achieve the desired resonance frequencies. The shown embodiments are only for exemplifying purposes and are not intended to limit the
 20 scope of the invention.

Fig. 4 illustrates a second embodiment of the antenna device according to the invention, comprising the first antenna 110 of Fig. 3 and a second antenna 120a-b. The second antenna comprises first and second printed meander
 25 monopole antenna branches 120a-b of strips of conducting material provided on the support element 111. The monopole antenna branches 120a-b are physically separated to provide spatial diversity. The distance between the monopole antenna branches 120a-b is preferably at least $\frac{1}{4}$ wavelength
 30 of the signal for which said antenna is adapted. With appropriate physical distance between the first and second monopole antenna branch 120a-b a correlation coefficient below 0.1 is achieved, which provides a good diversity gain. The length of each of the monopole antenna branches
 35 120a-b are selected so as to allow said antenna 120,a-b to

be tuned to a resonance frequency band different than the frequency bands of the first antenna 110. The frequency band of the monopole antenna is e.g. a W-LAN 2.4 GHz frequency band. The first and second monopole antenna branch 120a-b have first and second terminals 121a-b, respectively, for exchanging signals with the transmitter/receiver circuitry within the card device 1.

The pattern of the second antenna is not limited to meander monopole antennas. The second antenna may be provided as meander antennas or PIFA (Planar Inverted F Antenna) antennas. Also, it is not necessary or required that the second antenna 120a-b is a diversity antenna.

The terminals 114, 121a-b may be directly connected to the circuitry of the card device 1, which may be provided on a PCB (Printed Circuit Board) 130, by a number of different connection techniques, such as by soldering directly to the PCB 130, by pogo-pins, or leaf spring contacts.

If the impedance of the antennas is matched to the circuitry of the PCB 130, such as having an impedance of 50 ohm, no antenna matching circuitry is needed and the antenna device may be directly connected to the circuitry of the card device 1.

The antenna device comprises the support element 111, upon which the first and second antennas 110, 120a-b are provided. In one embodiment of the invention, the support element 111 is a flexible dielectric film. Suitable film materials are commercially available from Rogers Corporation, Advanced Circuit Materials Division, 100 N Dobson Road, Chandler, AZ-85224, USA, or alternatively from Freudenberg Mectec GmbH, Headquarters, D-69465 Weinheim/bergstrasse, Germany. Such flexible dielectric films are utterly thin. The typical thickness ranges are from about 70 μm to about 400 μm .

Thus, the thickness of the protruding member 11 may also be thin, and is essentially limited by the preferred thickness of said member 11. In the embodiment of Figs. 4 and 5, the length of the film is approximately 15 mm. Other lengths may be provided, and is dependent of the actual shape of the antenna branches. The flexible dielectric film may be provided with an adhesive for fastening said film to an inner surface of the protruding member 11. Because the film is flexible, it can take a wide range of different geometric shapes. The shapes may conform to the geometric shape of the inner surface of the protruding member 11, depending upon design considerations.

The protruding member 11 may be provided with two separate connectable portions having a cavity therebetween. The flexible film may be adhered to at least one of the inner surfaces of said portions. Alternatively, said film is provided on an outer surface of the protruding member 11 and may be covered by a protective layer. The protruding member 11 may alternatively be provided as a single unit comprising the flexible film.

The conductive strips of the antennas 110, 120a-b may be formed on the support element 111 by printing, etching, carving, soldering or any other suitable method.

Alternatively, the conductive strips of the antennas 110, 120a-b may be formed directly on an inner surface of the protruding member 11 forming the support element 111. The strips may be provided by e.g. an electroplating technique or a MID (Mould-Interconnect-Device) production technique, wherein the conductive material is selectively provided directly on the support element 111.

The housing 10 and the protruding member 11 may be provided using a injection-moulding technique, followed by a laser activation of metallic seeds on the inner surface of the protruding member 11. Finally, the surface having the seeds is immersed into a metallization bath, wherein a

conductive pattern of e.g. Cu, Ni, Au etc. may be formed. By forming the conductive pattern directly within the protruding member 11, the geometric shape of the antenna has an excellent conformance to the geometric shape of the inner surface of the protruding member 11.

The support element 111 may still alternatively comprise a PCB, which may form part of the PCB 130 of the card device 1. The geometric shape of the protruding member 11 is then adapted to the geometric shape of the PCB, which in general will be elongated in the direction of insertion and retraction X into the card slot. Alternatively, the PCB is a flexible PCB, which may be conformed to the geometrical shape of the protruding member 11.

When the card device 1 is inserted into a card slot, the protruding member 11 will protrude from said slot. Thus, it is desired to provide the antenna device within the protruding member 11 to provide good radiation characteristics. The antenna device may be provided as an integral part of the housing 10, and preferably within the protruding member 11.

The present invention has been described above with reference to specific embodiments. However, other embodiments than the above described are equally possible within the scope of the invention. The different features of the invention may be combined in other combinations than those described. The invention is only limited by the appended patent claims.

ABSTRACT

An antenna device for a computer card device, such as a PCMCIA type card. The antenna device comprises at least a first antenna formed as a trace on a support element, antenna output means, and a protruding member extending
5 from a housing of the card. The support element, e.g. a flexible dielectric film, has a geometric shape, which is conformed to the geometric shape of the protruding member.

10

To be published together with Fig. 1.




Fig. 1




Fig. 2a



Fig. 2b



Fig. 2c

3/3




Fig. 3




Fig. 4